

IN THE CLAIMS:

Please amend the claims as follows:

1. (Currently Amended) A weighting circuit for a receiver which is provided for receiving a multicarrier signal comprising carrier signals, comprising:
 - a memory storing a plurality of weighting coefficient sets,
 - a selector selecting one of the plurality of weighting coefficient sets stored in the memory on the basis of an expected spurious signal energy in the received signal, and
 - an estimation unit calculating said expected spurious signal energy using cross correlation between the received signal and a spurious signal to be expected which has been phase-shifted through 90° ;
 - wherein the weighting circuit weights the carrier signal such that the spurious signal energy is of equal magnitude for all weighted carrier signals; [[and]]
 - wherein said expected spurious signal energy is set externally; and
 - wherein the memory is programmable via an interface connected to said memory through a plurality of internal data lines.
2. (Previously Presented) The weighting circuit as claimed in claim 1, wherein the weighting circuit has at least one multiplier which multiplies an associated carrier signal by a stored weighting coefficient from the selected weighting coefficient set.

Serial No.: 10/566,531

3. (Canceled)
4. (Previously Presented) The weighting circuit as claimed in claim ~~[[3]]~~1, wherein the multicarrier signal is broken down into the carrier signals by a computation circuit.
5. (Previously Presented) The weighting circuit as claimed in claim 4, wherein the computation circuit is a Fast Fourier Transformation circuit.
6. (Previously Presented) The weighting circuit as claimed in claim 5, wherein the carrier signals broken down by the computation circuit are buffer-stored in a buffer store.
- 7-12. (Canceled)